



SIL'ON[®] **ELEGANT** 300

Acrylic Interior Wallpainting

Description : **SIL'ON[®] ELEGANT 300** is a Interior wall painting for building, housing with high quality, formulated from 100 % acrylic resin, special pigment which is have a good colour durability, anti moss and fungus resistance. **SIL'ON[®] ELEGANT 300** has a good adhesion.

Advantage : - Good adheres to all surfaces.
- Moss and fungus resistant.
- Available in several colours, suitable for decorative purposes.
- Washable and Weather resistant

Technical Data : Chemical base : Acrylic
Viscosity at 30 C : ± 15.000 cps
Specific gravity : $\pm 1,45$ kg/litre
Colour : Variety
Packaging : 25 kg pail
5 kg gallon
Theoretical Spreading : 8 – 12 m² /kg/coat, teoritis (depend on application and porosity of surface).
Dry time : ± 2 hours (ambient temperature 25°C)

Storage : Store in cool and dry place. If the original packaging is unbroken, the substrate will remain active for up to one year.

Application : Clean the surface out of dust, loose particles, oil, rust or moss. For the best result use **SIL'ON[®] ALKALI SEALER** for primer layer. For the first layer of top coat, mix **SIL'ON[®] ELEGANT 300** with water.
For the second layer mix **SIL'ON[®] ELEGANT 300** with water if needed. Apply the second layer after the first layer dry.
Do not use metal tools for applying **SIL'ON[®] ELEGANT 300**.

MERGUSA

Jl. Teluk Betung 42, 2nd floor
Jakarta 10230
www.mergusa.co.id
e-mail:
mergusachem@cbn.net.id

TELP. 62 21 3911369

FAX. 62 21 3911372

The colour chips on this chart are colour matched representations rather than exact matches. The exact appearance of any colour will vary due to differences in generic type, sheen, texture, application method and lighting conditions.