



SIL'ON[®] SUPER SHIELD 100

Acrylic Exterior Wallpainting

Description : **SIL'ON[®] SUPER SHIELD 100** is a exterior wall painting for building, housing with high quality, formulated from 100 % acrylic resin, special pigment which is have a good colour durability, anti moss and fungus resistance.
SIL'ON[®] SUPER SHIELD 100 resist to ultra violet and weather which has a good adhesion.

Advantage : - Good adheres to all surfaces.
- Alkali, moss and fungus resistant.
- Ultra violet and weather resistant.
- Available in several colours, suitable for decorative purposes.

Technical Data : Chemical base : Acrylic
Viscosity at 30 C : ± 10.000 cps
Specific gravity : $\pm 1,25$ kg/litre
Colour : Variety
Packaging : 25 kg pail
5 kg gallon
Theoretical Spreading : $10 - 12 \text{ m}^2 / \text{kg}/\text{coat}$, teoritis
(depend on application and porosity of surface).
Dry time : ± 2 hours (ambient temperature 25°C)

Storage : Store in cool and dry place. If the original packaging is unbroken, the substrate will remain active for up to one year.

Application : Clean the surface out of dust, loose particles, oil, rust or moss. For the best result use **SIL'ON[®] ALKALI SEALER** for primer layer.
For the first layer of top coat, mix **SIL'ON[®] SUPER SHIELD 100** with water.
For the second layer mix **SIL'ON[®] SUPER SHIELD 100** with water if needed.
Apply the second layer after the first layer dry.
Do not use metal tools for applying **SIL'ON[®] SUPER SHIELD 100**.