



# SIL'ON®

## Waterproofing Coating

**Description** : **SIL'ON®** is a sealing compound for the construction industry, formulated from acrylic resin, special pigment, plus anti moss and fungal agents, **SIL'ON®** has a good adhesion properties and highly elastic making it very suitable for overcoming problems of humidity and leakage in walls, concrete roofs, asbestos construction etc.

**Advantage** : Adheres well to all surfaces  
- Elastic  
- Moss and fungus resistant  
- Available in several colours, suitable for decorative purposes

**Technical Data** : Chemical base : Acrylic  
Viscosity at 30 C<sup>0</sup> : 22,000 CPs  
(Brookfield; RVT; #7/20)  
Specific gravity : 1.3 kg/litre  
Colour : Variety  
Packaging : 1 kg plastic can  
5 kg plastic gallon  
25 kg plastic pail  
Recommended rate of : 1.5 kg/m<sup>2</sup>

**Storage** : Store in cool and dry place. If the original packaging is unbroken, the substrate will remain active for up to one year.

**Application** : Clean the surface to be coated of dust, loose particles, oil, rust or moss. For the first layer, to fill pores in the surface, mix **SIL'ON®** with water in a ratio of 2:1. when the first layer is dry, apply a second layer to cover the first layer, using a paintbrush or roller. When apply **SIL'ON®**, do not use metal tools other those made from stainless steel.

### MERGUSA

Jl. Teluk Betung 42, 2<sup>nd</sup> floor  
Jakarta **10230**  
www.mergusa.co.id  
e-mail:  
[mergusachem@cbn.net.id](mailto:mergusachem@cbn.net.id)

**TELP. 62 21 3911369**  
**FAX. 62 21 3911372**

The colour chips on this chart are colour matched representations rather than exact matches. The exact appearance of any colour will vary due to differences in generic type, sheen, texture, application method and lighting conditions.